



Mini Heater, R32, Horizontal design, Plastic + Metal cabinet

Poolclub Model		MINI Q25	MINI Q45	MINI Q55
Advised pool volume (with pool cover)	m ³	0-10	5-16	10-20
Air 28°C, Water 28°C, Humidity 80%				
Heat Output	kW	2,5	4,2	5,5
Power Consumption	kW	0,59	1,00	1,31
COP		4,2	4,2	4,2
Air 15°C, Water 26°C, Humidity 70%				
Heat Output	kW	1,9	3,2	4,2
Power Consumption	kW	0,56	0,91	1,2
COP		3,4	3,5	3,5
Voltage		220-240V/50Hz/1Ph		
Rated Current	A	2,6	4,4	5,8
Fuse Current	A	7,5	13	16
Advised water flux	m ³ /h	2	2	2.5-3.2
Water Pressure Drop	KPa	4	2,5	8,5
Condenser		Titanium exchanger in PVC		
Water pipe in-out	mm	32 or 38mm		
Noise level(10m)	dB(A)	48	46	46
Noise level(1m)	dB(A)	57	55	55
Net Weight	kg	22	33	33
Gross Weight	kg	24	35	35
Net Dimension	mm	328*346*420	437*437*521	
Packing Dimension	mm	385*480*480	495*570*585	

The data above is for reference. Please refer to the nameplate on the unit.